



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

EMERGENCY OVERVIEW

DANGER!

EXTREMELY FLAMMABLE GAS - MAY CAUSE FLASH FIRE OR EXPLOSION!

High concentrations may exclude oxygen and cause dizziness and suffocation.
Contact with pressurized vapor may cause frostbite or freeze burn.



NFPA 704 (Section 16)

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Hess Corporation
1 Hess Plaza
Woodbridge, NJ 07095-0961

EMERGENCY TELEPHONE NUMBER:
COMPANY CONTACT (business hours):
MSDS Internet Website:

CHEMTREC (800) 424-9300
Corporate EHS 732-750-6000
www.hess.com

SYNONYMS: Compressed Natural Gas (CNG); Dry Natural Gas ; Methane; Pipeline Spec Gas;
Processed Gas; Residue Gas; Sweet Natural Gas; Treated Gas

See Section 16 for abbreviations and acronyms.

2. COMPOSITION and CHEMICAL INFORMATION ON INGREDIENTS

INGREDIENT NAME (CAS No.)	CONCENTRATION PERCENT BY WEIGHT
Natural Gas, dry (68410-63-9)	100
Methane (74-82-8)	<90
Ethane (74-84-0)	<balance>

A complex mixture of light gases separated from raw natural gas consisting of aliphatic hydrocarbons having carbon numbers in the range of C1 through C4, predominantly methane (C1) and ethane (C2); may contain carbon dioxide (CO₂). Odorized with trace amounts of odorant (see Section 9). This is for natural gas that has been processed and is in commerce.

3. HAZARDS IDENTIFICATION

EYES

Not irritating. However, contact with pressurized vapor may cause frostbite, freeze burns, and permanent eye damage.

SKIN

Not irritating. Direct contact to skin or mucous membranes with pressurized vapor may cause freeze burns and frostbite. Signs of frostbite include a change in the color of the skin to gray or white, possibly followed by blistering. Skin may become inflamed and painful.

INGESTION

Risk of ingestion is extremely unlikely.



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

INHALATION

This product is considered to be non-toxic by inhalation. Inhalation of high concentrations may cause central nervous system depression such as dizziness, drowsiness, headache, and similar narcotic symptoms, but no long-term effects. Numbness, a "chilly" feeling, and vomiting have been reported from accidental exposures to high concentrations.

This product is a simple asphyxiant. In high concentrations it will displace oxygen from the breathing atmosphere, particularly in confined spaces. Signs of asphyxiation will be noticed when oxygen is reduced to below 16%, and may occur in several stages. Symptoms may include rapid breathing and pulse rate, headache, dizziness, visual disturbances, mental confusion, incoordination, mood changes, muscular weakness, tremors, cyanosis, narcosis and numbness of the extremities. Unconsciousness leading to central nervous system injury and possibly death will occur when the atmospheric oxygen concentration is reduced to about 6% to 8% or less.

WARNING: The burning of any hydrocarbon as a fuel in an area without adequate ventilation may result in hazardous levels of combustion products, including carbon monoxide, and inadequate oxygen levels, which may cause unconsciousness, suffocation, and death.

CHRONIC EFFECTS and CARCINOGENICITY

None expected - see Section 11.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing conditions of the heart, lungs, and blood may have increased susceptibility to symptoms of asphyxia.

4. FIRST AID MEASURES

EYES

In case of freeze burn cover eyes to protect from light. Seek immediate medical attention.

SKIN

In case of frostbite or freeze burns seek immediate medical attention.

INGESTION

Though risk of ingestion is extremely unlikely, in case of frostbite or freeze burns due to oral exposure seek immediate medical attention.

INHALATION

This product is considered to be non-toxic by inhalation. Inhalation of high concentrations may cause central nervous system depression such as dizziness, drowsiness, headache, and similar narcotic symptoms, but no long-term effects. Numbness, a "chilly" feeling, and vomiting have been reported from accidental exposures to high concentrations.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: (NFPA Natural Gas)

FLASH POINT:	Flammable gas
AUTOIGNITION POINT:	900 - 1170 °F (482 - 632 °C)
OSHA/NFPA FLAMMABILITY CLASS:	FLAMMABLE GAS
LOWER EXPLOSIVE LIMIT (%):	3.8 - 6.5
UPPER EXPLOSIVE LIMIT (%):	13 - 17



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

FIRE AND EXPLOSION HAZARDS

Dangerous fire and explosion hazard when exposed to heat, sparks or flame. Natural gas is lighter than air and may travel long distances to a point of ignition and flash back. Container may explode in heat or fire. Liquefied Natural Gas (LNG) releases flammable gas at well below ambient temperatures and readily forms a flammable mixture with air.

EXTINGUISHING MEDIA

Dry chemical, carbon dioxide, Halon or water. However, fire should not be extinguished unless flow of gas can be immediately stopped.

FIRE FIGHTING INSTRUCTIONS

Gas fires should not be extinguished unless flow of gas can be immediately stopped. Shut off gas source and allow gas to burn out. If spill or leak has not ignited, determine if water spray may assist in dispersing gas or vapor to protect personnel attempting to stop leak.

Use water to cool equipment, surfaces and containers exposed to fire and excessive heat. For large fire the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure.

Isolate area, particularly around ends of storage vessels. Let vessel, tank car or container burn unless leak can be stopped. Withdraw immediately in the event of a rising sound from a venting safety device. Large fires typically require specially trained personnel and equipment to isolate and extinguish the fire.

Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing.

See Section 16 for the NFPA 704 Hazard Rating.

6. ACCIDENTAL RELEASE MEASURES

ACTIVATE FACILITY'S SPILL CONTINGENCY OR EMERGENCY RESPONSE PLAN.

Evacuate nonessential personnel and secure all ignition sources. No road flares, smoking or flames in hazard area. Consider wind direction, stay upwind, if possible. Evaluate the direction of product travel. Cold vapor cloud may be white, but color will dissipate as cloud disperses - fire and explosion hazard is still present!

Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering.

7. HANDLING and STORAGE

HANDLING and STORAGE PRECAUTIONS

Keep away from flame, sparks and excessive temperatures. Store only in approved containers. Bond and ground containers. Use only in well ventilated areas. See also applicable OSHA regulations for the handling and storage of this product, including, but not limited to, 29 CFR 1910.110 Storage and Handling of Liquefied Petroleum Gases.



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

8. EXPOSURE CONTROLS and PERSONAL PROTECTION

EXPOSURE LIMITS

Components (CAS No.)	Source	Exposure Limits		Note
		TWA/STEL		
Natural Gas, dry (68410-63-9)	OSHA ACGIH		None established by OSHA or ACGIH Simple asphyxiant; exposure limited by oxygen and flammability	
Methane (74-82-8)	OSHA ACGIH		None established by OSHA or ACGIH Simple asphyxiant; exposure limited by oxygen and flammability	
Ethane (74-84-0)	OSHA ACGIH		None established by OSHA or ACGIH Simple asphyxiant; exposure limited by oxygen and flammability	

ENGINEERING CONTROLS

Use adequate ventilation to keep gas concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. Use explosion-proof equipment and lighting in classified/controlled areas.

EYE/FACE PROTECTION

Splash-proof safety goggles and/or faceshield for protection from pressurized gas

SKIN PROTECTION

Wear apron, faceshield, and cold-impervious, insulating gloves may protect from pressurized gas.

RESPIRATORY PROTECTION

Use a NIOSH/MSHA approved positive-pressure, supplied air respirator with escape bottle or self-contained breathing apparatus (SCBA) for gas concentrations above occupational exposure limits, for potential for uncontrolled release, if exposure levels are not known, or in an oxygen-deficient atmosphere.

CAUTION: Flammability limits (i.e., explosion hazard) should be considered when assessing the need to expose personnel to concentrations requiring respiratory protection.

Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection.

9. PHYSICAL and CHEMICAL PROPERTIES

APPEARANCE

Colorless gas. Cold vapor cloud may be white but the lack of visible gas cloud does not indicate absence of gas.

ODOR

Natural gas has a distinctive, disagreeable "natural gas" type odor when treated with an odorizing agent (typically < 0.1% ethyl mercaptan).

BASIC PHYSICAL PROPERTIES (for methane)

BOILING POINT: -259 °F (-162 °C)
VAPOR PRESSURE: 40 atm. @ -187 °F (-86 °C)
VAPOR DENSITY (air = 1): 0.6
SPECIFIC GRAVITY (H₂O = 1): 0.4 @ -263 °F (-164 °C)
SOLUBILITY (H₂O): 3.5%



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

10. STABILITY and REACTIVITY

STABILITY: Stable. Hazardous polymerization will not occur.

CONDITIONS TO AVOID and INCOMPATIBLE MATERIALS

Keep away from strong oxidizers, ignition sources and heat.

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

11. TOXICOLOGICAL PROPERTIES

ACUTE TOXICITY

Methane and ethane, the main components of natural gas, are considered practically inert in terms of physiological effects. At high concentrations these materials act as simple asphyxiants and may cause death due to lack of oxygen.

CARCINOGENICITY

OSHA: NO **IARC:** NO **NTP:** NO **ACGIH:** NO

12. ECOLOGICAL INFORMATION

Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

13. DISPOSAL CONSIDERATIONS

Consult federal, state and local waste regulations to determine appropriate disposal options.

14. TRANSPORTATION INFORMATION (

PROPER SHIPPING NAME: Natural Gas, Compressed (*with high methane content*)

HAZARD CLASS and PACKING GROUP: 2.1

DOT IDENTIFICATION NUMBER: UN 1971

DOT SHIPPING LABEL: FLAMMABLE GAS

Placard:



15. REGULATORY INFORMATION

U.S. FEDERAL, STATE, and LOCAL REGULATORY INFORMATION

This product and its constituents listed herein are on the EPA TSCA Inventory. Any spill or uncontrolled release of this product, including any substantial threat of release, may be subject to federal, state and/or local reporting requirements. This product and/or its constituents may also be subject to other regulations at the state and/or local level. Consult those regulations applicable to your facility/operation.

CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT)

This product does not contain any chemicals subject to the reporting requirements of CERCLA Section 103 or SARA 304. In addition, the CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts natural gas and synthetic gas usable for fuel and any indigenous components of such from the CERCLA Section 103 reporting requirements.

SARA SECTION 311/312 - HAZARD CLASSES

<u>ACUTE HEALTH</u>	<u>CHRONIC HEALTH</u>	<u>FIRE</u>	<u>SUDDEN RELEASE OF PRESSURE</u>	<u>REACTIVE</u>
--	--	X	X	--



MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

SARA SECTION 313 - SUPPLIER NOTIFICATION

This product does not contain any chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

CANADIAN REGULATORY INFORMATION

Class A (Compressed Gas) Class B, Division 1 (Flammable Gas)

CALIFORNIA PROPOSITION 65 LIST OF CHEMICALS

This product and its components are not listed on the Proposition 65 "List of Chemicals" required by the California Safe Drinking Water and Toxic Enforcement Act of 1986:

16. OTHER INFORMATION

Table with 2 columns: NFPA® HAZARD RATING and values for HEALTH, FIRE, and REACTIVITY.

Refer to NJPA 704 "Identification of the Fire Hazards of Materials" for further information

Table with 2 columns: HMIS® HAZARD RATING and values for HEALTH, FIRE, and PHYSICAL.

SUPERSEDES MSDS DATED: 08/12/1998

ABBREVIATIONS:

AP = Approximately < = Less than > = Greater than
N/A = Not Applicable N/D = Not Determined ppm = parts per million

ACRONYMS:

Table listing acronyms and their full names: ACGIH, AIHA, ANSI, API, CERCLA, DOT, EPA, HMIS, IARC, MSHA, NFPA, NIOSH, NOIC, NTP, OPA, OSHA, PEL, RCRA, REL, SARA, SCBA, SPCC, STEL, TLV, TSCA, TWA.

AMERADAHESSCORPORATION

MATERIAL SAFETY DATA SHEET

Natural Gas (odorized)

MSDS No. 8010

WEEL Workplace Environmental Exposure
Level (AIHA)

WHMIS Canadian Workplace Hazardous
Materials Information System

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.