



# Safety Data Sheet

**Material Name:** Light Cycle Oil

**SDS No. 0326**  
US GHS

**Synonyms:** Crude Petroleum: Sour Crude

## \*\*\* Section 1 - Product and Company Identification \*\*\*

### Manufacturer Information

Hess Corporation  
1 Hess Plaza  
Woodbridge, NJ 07095-0961

Phone: 732-750-6000 Corporate EHS  
Emergency # 800-424-9300 CHEMTREC  
[www.hess.com](http://www.hess.com) (Environment, Health, Safety Internet Website)

## \*\*\* Section 2 - Hazards Identification \*\*\*

### GHS Classification:

Flammable Liquids - Category 3  
Acute Toxicity, Inhalation - Category 4  
Skin Corrosion/Irritation – Category 2  
Eye Damage/Irritation – Category 2B  
Carcinogenicity - Category 1B  
Specific Target Organ Toxicity (Single Exposure) – Category 3 (respiratory irritation, narcosis)  
Specific Target Organ Toxicity (Repeat Exposure) – Category 1 (liver, kidneys, blood, nervous system)  
Aspiration Hazard – Category 1  
Hazardous to the Aquatic Environment, Acute Hazard – Category 2

### GHS LABEL ELEMENTS

#### Symbol(s)



#### Signal Word

DANGER

#### Hazard Statements

Flammable liquid and vapor.  
Harmful if inhaled.  
Causes skin irritation.  
Causes eye irritation.  
May cause cancer.  
Suspected of causing genetic defects.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
Causes damage to liver, kidneys, blood, nervous system through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.  
Toxic to aquatic life.

# Safety Data Sheet

Material Name: Light Cycle Oil

## Precautionary Statements

### Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Do not breathe fume/mist/vapors/spray.  
Do not eat, drink, or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wash hands and forearms thoroughly after handling.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Avoid release to the environment.

### Response

In case of fire: Use water spray, fog or foam.  
If on skin (or hair): Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs, get medical advice/attention.  
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
If exposed or concerned: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.  
If swallowed: Immediately call a poison center or doctor/physician if you feel unwell. Do NOT induce vomiting.

### Storage

Store in a well-ventilated place.  
Keep cool. Store locked up.  
Keep container tightly closed.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

## \* \* \* Section 3 - Composition / Information on Ingredients \* \* \*

| CAS #      | Component                                      | Percent |
|------------|--|---------|
| 64741-59-9 | Petroleum distillates, light catalytic cracked | 100     |

A complex combination of hydrocarbons produced by the distillation of products from the fluidized catalytic cracking (FCC) process with carbon numbers in the range C9 to C25, boiling in the approximate range of 340 to 700 °F.

# Safety Data Sheet

Material Name: Light Cycle Oil

## \*\*\* Section 4 - First Aid Measures \*\*\*

### First Aid: Eyes

In case of contact with eyes, immediately flush with clean, low-pressure water for at least 15 min. Hold eyelids open to ensure adequate flushing. Seek medical attention.

### First Aid: Skin

Remove contaminated clothing. Wash contaminated areas thoroughly with soap and water or with waterless hand cleanser. Obtain medical attention if irritation or redness develops. Thermal burns require immediate medical attention depending on the severity and the area of the body burned.

### First Aid: Ingestion

DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Monitor for breathing difficulties. Small amounts of material which enter the mouth should be rinsed out until the taste is dissipated.

### First Aid: Inhalation

Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

## \*\*\* Section 5 - Fire Fighting Measures \*\*\*

### General Fire Hazards

See Section 9 for Flammability Properties.

Vapors may be ignited rapidly when exposed to heat, spark, open flame or other source of ignition. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

### Hazardous Combustion Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

### Extinguishing Media

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO<sub>2</sub>, water spray, fire fighting foam, or gaseous extinguishing agent.

LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

### Unsuitable Extinguishing Media

None

### Fire Fighting Equipment/Instructions

Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other fire fighting equipment. Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing. Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam.

# Safety Data Sheet

Material Name: Light Cycle Oil

## \*\*\* Section 6 - Accidental Release Measures \*\*\*

### Recovery and Neutralization

Carefully contain and stop the source of the spill, if safe to do so.

### Materials and Methods for Clean-Up

Take up with sand or other oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container for reclamation or disposal.

### Emergency Measures

Evacuate nonessential personnel and remove or secure all ignition sources. Consider wind direction; stay upwind and uphill, if possible. Evaluate the direction of product travel, diking, sewers, etc. to confirm spill areas. Product may release substantial amounts of flammable vapors and gases (e.g., methane, ethane, and propane), at or below ambient temperature depending on source and process conditions and pressure.

### Personal Precautions and Protective Equipment

Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

### Environmental Precautions

Protect bodies of water by diking, absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of fire fighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection - do not discharge solid water stream patterns into the liquid resulting in splashing.

### Prevention of Secondary Hazards

None

## \*\*\* Section 7 - Handling and Storage \*\*\*

### Handling Procedures

Handle as a combustible liquid. Keep away from heat, sparks, excessive temperatures and open flame! No smoking or open flame in storage, use or handling areas. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion.

Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil) is loaded into tanks previously containing low flash point products (such as this product) - see API Publication 2003, "Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents."

### Storage Procedures

Keep containers closed and clearly labeled. Use approved vented storage containers. Empty product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition.

Store in a well-ventilated area. This storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". Avoid storage near incompatible materials. The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks."

### Incompatibilities

Keep away from strong oxidizers; Viton ®; Fluorel ®

# Safety Data Sheet

Material Name: Light Cycle Oil

## \*\*\* Section 8 - Exposure Controls / Personal Protection \*\*\*

### Component Exposure Limits

ACGIH, OSHA, and NIOSH have not developed exposure limits for any of this product's components.

### Engineering Measures

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.

### Personal Protective Equipment: Respiratory

A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited.

Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.

### Personal Protective Equipment: Hands

Gloves constructed of nitrile or neoprene are recommended.

### Personal Protective Equipment: Eyes

Safety glasses or goggles are recommended where there is a possibility of splashing or spraying.

### Personal Protective Equipment: Skin and Body

Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure. Consult manufacturer specifications for further information.

## \*\*\* Section 9 - Physical & Chemical Properties \*\*\*

|  |                               |  |                                 |
|--|-------------------------------|--|---------------------------------|
| <b>Appearance:</b>                     | Straw-colored, water-like     | <b>Odor:</b>                           | Mild, petroleum distillate odor |
| <b>Physical State:</b>                 | Liquid                        | <b>pH:</b>                             | ND                              |
| <b>Vapor Pressure:</b>                 | 0.009 psia @ 70 °F (21 °C)    | <b>Vapor Density:</b>                  | >1.0                            |
| <b>Boiling Point:</b>                  | 340 to 700 °F (171 to 371 °C) | <b>Melting Point:</b>                  | ND                              |
| <b>Solubility (H2O):</b>               | Negligible                    | <b>Specific Gravity:</b>               | AP 0.9 @ 60°F (16°C)            |
| <b>Evaporation Rate:</b>               | Slow; varies with conditions  | <b>VOC:</b>                            | ND                              |
| <b>Percent Volatile:</b>               | 100%                          | <b>Octanol/H2O Coeff.:</b>             | ND                              |
| <b>Flash Point:</b>                    | 100 °F (38 °C) minimum        | <b>Flash Point Method:</b>             | PMCC                            |
| <b>Upper Flammability Limit (UFL):</b> | ND                            | <b>Lower Flammability Limit (LFL):</b> | ND                              |
| <b>Burning Rate:</b>                   | ND                            | <b>Auto Ignition:</b>                  | ND                              |

## \*\*\* Section 10 - Chemical Stability & Reactivity Information \*\*\*

### Chemical Stability

This is a stable material.

### Hazardous Reaction Potential

Will not occur.

### Conditions to Avoid

Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.

# Safety Data Sheet

**Material Name:** Light Cycle Oil

## Incompatible Products

Keep away from strong oxidizers; Viton ®; Fluorel ®

## Hazardous Decomposition Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

## \* \* \* Section 11 - Toxicological Information \* \* \*

### Acute Toxicity

#### A: General Product Information

Harmful if swallowed.

#### B: Component Analysis - LD50/LC50

**Petroleum distillates, light catalytic cracked (64741-59-9)**

Inhalation LC50 Rat 3400 mg/m<sup>3</sup> 4 h; Inhalation LC50 Rat 4.65 mg/L 4 h; Oral LD50 Rat 3200 mg/kg; Dermal LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg

### Potential Health Effects: Skin Corrosion Property/Stimulativeness

Practically non-toxic if absorbed following acute (single) exposure. May cause skin irritation with prolonged or repeated contact. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly. Rare, precancerous warts on the forearms, backs of hands and scrotum have been reported from prolonged or repeated skin contact.

### Potential Health Effects: Eye Critical Damage/ Stimulativeness

Contact with eyes may cause moderate to severe irritation.

### Potential Health Effects: Ingestion

Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest, and death may occur.

### Potential Health Effects: Inhalation

Excessive exposure may cause irritations to the nose, throat, lungs and respiratory tract. Central nervous system (brain) effects may include headache, dizziness, loss of balance and coordination, unconsciousness, coma, respiratory failure, and death.

WARNING: the burning of any hydrocarbon as a fuel in an area without adequate ventilation may result in hazardous levels of combustion products, including carbon monoxide, and inadequate oxygen levels, which may cause unconsciousness, suffocation, and death.

### Respiratory Organs Sensitization/Skin Sensitization

This product is not reported to have any skin sensitization effects.

### Generative Cell Mutagenicity

Material of similar composition has been positive in a mutagenicity study.

### Carcinogenicity

#### A: General Product Information

May cause cancer.

Studies have shown that similar products produce skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation.

# Safety Data Sheet

**Material Name: Light Cycle Oil**

This product is similar to Diesel Fuel. IARC classifies whole diesel fuel exhaust particulates as probably carcinogenic to humans (Group 2A) and NIOSH regards it as a potential cause of occupational lung cancer based on animal studies and limited evidence in humans.

## **B: Component Carcinogenicity**

None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

## **Reproductive Toxicity**

This product is not reported to have any reproductive toxicity effects.

## **Specified Target Organ General Toxicity: Single Exposure**

This product is not reported to have any specific target organ general toxicity single exposure effects.

## **Specified Target Organ General Toxicity: Repeated Exposure**

This product is not reported to have any specific target organ general toxicity repeat exposure effects.

## **Aspiration Respiratory Organs Hazard**

The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

## \* \* \* Section 12 - Ecological Information \* \* \*

### **Ecotoxicity**

#### **A: General Product Information**

Keep out of sewers, drainage areas and waterways. Report spills and releases, as applicable, under Federal and State regulations.

#### **B: Component Analysis - Ecotoxicity - Aquatic Toxicity**

**Petroleum distillates, light catalytic cracked (64741-59-9)**

##### **Test & Species**

96 Hr LC50 Brachydanio rerio

##### **Conditions**

7.3 mg/L [semi-static]

### **Persistence/Degradability**

No information available.

### **Bioaccumulation**

No information available.

### **Mobility in Soil**

No information available.

## \* \* \* Section 13 - Disposal Considerations \* \* \*

### **Waste Disposal Instructions**

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

### **Disposal of Contaminated Containers or Packaging**

Dispose of contents/container in accordance with local/regional/national/international regulations.

## \* \* \* Section 14 - Transportation Information \* \* \*

### **DOT Information**

**Shipping Name:** Gas oil

**UN #: 1202 Hazard Class: 3 Packing Group: III**

# Safety Data Sheet

**Material Name:** Light Cycle Oil

**Placard:**



**\*\*\* Section 15 - Regulatory Information \*\*\***

**Regulatory Information**

**Component Analysis – Inventory**

None of this products components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

**SARA Section 311/312 – Hazard Classes**

|                     |                       |             |                                   |                 |
|---------------------|-----------------------|-------------|-----------------------------------|-----------------|
| <u>Acute Health</u> | <u>Chronic Health</u> | <u>Fire</u> | <u>Sudden Release of Pressure</u> | <u>Reactive</u> |
| X                   | X                     | X           | --                                | --              |

**SARA SECTION 313 - SUPPLIER NOTIFICATION**

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

**State Regulations**

**Component Analysis - State**

None of this product's components are listed on the state lists from CA, MA, MN, NJ, PA, or RI.

**Component Analysis - WHMIS IDL**

No components are listed in the WHMIS IDL.

**Additional Regulatory Information**


**Component Analysis - Inventory**

| Component                                      | CAS #      | TSCA | CAN | EEC    |
|--|------------|------|-----|--------|
| Petroleum distillates, light catalytic cracked | 64741-59-9 | Yes  | DSL | EINECS |

**\*\*\* Section 16 - Other Information \*\*\***

**NFPA® Hazard Rating**

|            |   |
|------------|---|
| Health     | 1 |
| Fire       | 2 |
| Reactivity | 0 |



**HMIS® Hazard Rating**

|          |    |          |
|----------|----|----------|
| Health   | 1* | Slight   |
| Fire     | 2  | Moderate |
| Physical | 0  | Minimal  |

\*Chronic



# Safety Data Sheet

**Material Name: Light Cycle Oil**

## Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

## Literature References

None

## Other Information

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.

End of Sheet